



AA903C WALL MASTER STATION



GENERAL:

Loudspeaking hands-free operation.

Brushed aluminum front plate.

Voice controlled "Duplex" communication.

Full keypad with access to all system features.

Sensitive electret microphone.

Volume control on front panel.

Handset connector on front panel.

Operates with Ring-Master Systems
CB901, CB901CA, CB901EX, RM5000 and RM5000EX.

Made in USA

DESCRIPTION:

The AA903C has speaker and microphone for normal hands free speech with a range of 3-5 meters (10-15 feet). The stations key board consists of 10 numeric dialing keys (DTMF), push-to-talk key (T), cancel key (X), volume UP/DOWN keys, privacy key (P) and a microphone mute key (M). A status LED is used for indicating station-ON and Privacy. The station offers a module plug on the face plate for easy installation of the optional handset for confidential speaking

FEATURES:

All system features are accessed from the keypad.

Refer to documentation for features in the system used: CB901, RM5000, CB901EX or RM5000EX.

ORDERING INFORMATION:

AA903C Wall master station

BBF863 Flush back-box

BBS863 Surface back-box

BBD905 Desk back-box

GD501 Handset

TECHNICAL DATA AA903C

Operating Voltage:

20-27 V DC

Power Consumption:

150 mA max.

Dimensions (HWD):

250mm x 140mm x 40mm
(9.85" x 5.5" x 1.6")

Weight:

0.52 Kg (1.6 lb)

Central Exchange Connections:

Terminated in RJ45 Connector.
1 twisted pair (UTP) for audio/signaling.
1 twisted pair (UTP) for power.

Line Specifications:

Audio: Galvanic line,
Frequency range: 300-5000 hZ
Normal speech level: -12 dBm
Max. speech level: +4 dBm
DTMF signaling: -10 dBm



57 TRADE ZONE DRIVE
RONKONKOMA, N.Y. 11779 USA

Tel: 1-631-585-7464 mail@RingComm.com
Fax: 1-631-585-7410 http://www.RingComm.com

